

Optra M410/M412 Print Cartridge

Printer: Optra M410

Declaration of Yield:	Average Cartridge Yield	5000	standard pages
Declared yield value in accordance with ISO/IEC 19752			

Average 5876
Std Dev 138
90% Lower Confidence 5805

For questions concerning testing contact:

Lexmark International Inc.
 740 West New Circle Rd.
 Lexington, Ky. 40550 USA
 Attn: Laser Supplies Product Manager

	<u>start</u>	<u>stop</u>
Date tested	16-Dec-2004	21-Dec-2004
Number of cartridges in testing		12
Qty. of cartridges used in calculation		12
Shake Procedure	1st shake	At fade
	2nd shake	At fade
Print mode		Continuous
Number of printers tested		4
Media used		Boise Cascade X-9 - 20# - Letter
Paper feed orientation		Short Edge Feed (SEF)
Driver version		7.4.1
Operating system		Windows 2000
Application software		Adobe Acrobat version 6.01
Test page version		IS_19752_Testpage_Ver.200406.pdf

Cartridge testing data:		Temperature			Humidity			Cartridge Yield	Cart used in Calculation
Cartridge	Printer	Avg	Max	Min	Avg	Max	Min		
CAZ042890399	2546161	74	74	74	49	50	49	5,733	Y
CAZ042890369	2546164	74	74	74	49	50	49	5,656	Y
CAZ042890362	2546156	74	74	74	49	50	49	5,611	Y
CAZ042890350	2546499	74	74	74	49	50	49	5,957	Y
CAZ042890354	2546161	74	74	73	49	50	49	5,892	Y
CAZ042890367	2546164	74	74	73	49	50	49	5,870	Y
CAZ042890400	2546156	74	74	73	49	50	49	6,017	Y
CAZ042890380	2546499	74	74	73	49	50	49	5,938	Y
CAZ042890374	2546161	74	74	74	49	50	49	5,967	Y
CAZ042890385	2546164	74	74	74	49	50	49	5,877	Y
CAZ042890383	2546156	74	74	74	49	50	49	5,962	Y
CAZ042890351	2546499	74	74	74	49	50	49	6,036	Y

Comments and or exceptions:

